




BENTECH





Decorative cover-trim.



Angle profile.



- 1 Floor U-track
- 2 Cover-trim
- 3 13 mm plasterboard with vinyl coating
- 4 5 to 8 mm glazing or 44/2 laminated glazing (single or double)
- 5 Wooden door

H9 Relocatable Partitions

DESIGN

Partitions featuring an aluminium tubular frame with lacquered aluminium cover-trims which can be equipped with optional PVC cover-fillets. Any RAL colour possible. Assembly by using the HOYEZ system: self-centring by means of a spring and an eccentric screw. Correction of uneven levels thanks to Hoyez's patented telescopic element.

FILLINGS

- 2 x 13mm plasterboards or 2 x 12 to 15mm chipboards – Other fillings upon request.
- 85mm acoustic rolled panel sandwiched between the panels (PAR 85).
- Single or double glazing: 5 – 8mm and or 44/2 laminated glazing (8.8mm thick).
- Possible to incorporate blinds with vertical or horizontal blades.

COATINGS

Available in melamine faced or laminated finishes and vinyl coverings.

DOORS

- Aluminium doorcase with an acoustic seal at the periphery. Incorporation of the following types of doors:
 - Pre-painted or laminated wood doors, 40mm thick. Standard dimensions or with overpanel.
 - Clarit glass doors: clear glass or frosted.
 - Aluminium frame doors, 40mm thick, aluminium or PVC strips, choice of fillings.
 - Any dimension possible.

TECHNICAL FEATURES

- Thickness of the partition: 96mm.
- Standard modulation 1,200mm, any other modulation possible.
- Standard height: up to 6,000mm
- Correction of uneven levels or distorted bases of +/-12.5mm thanks to a telescopic element.

IMPORTANT

Sound insulation:
from 42 to 50 dB Rw
CERFF Certificate # 223.8.017 (France)



BENTECH

